

Product Information

HERMA SPECIAL A4 removable labels/Movables® technology, opaque

(Specifications valid for removable file spine labels and repositionable opaque address labels)

- Self-adhesive labels on A4 sheets, reliable adhesion, residue-free removable. Fully opaque.
- The more versatile label. Labelling is now easier, more reliable and more flexible
- Movables® technology: stick on, peel off, stick on
- Reliable adhesion on a wide range of surfaces (smooth, dry, undamaged, dust-free)
- Residue-free removal without damaging the surface
- Problem-free repositioning, adhere again several times
- Fully opaque – nothing shines through
- Suitable for all laser printers, inkjet printers, copiers, multifunctional machines. Also suitable for colour laser printers and colour copiers. Excellent print results in black and colour
- All-around protective edge prevents adhesive deposits
- Optimum flatness and high flexibility ensure trouble-free running
- Edges are cleanly cut on all sides, avoiding paper dust
- Environmentally friendly: FSC® Mix Credit certified, chlorine-free bleached, solvent-free adhesive
- Free from plasticiser, PH neutral, acid-free, resistant to ageing (lifetime class LDK 24-85)
- Labels are 100% recyclable, dispose of as for waste paper, packaging made from recycled cardboard
- Free software solutions: www.herma.com/software

1. Label paper

High-quality special paper, white, wood-free. Made of chlorine-free pulp, FSC® Mix Credit certified. With purple reverse coat. The paper is of captivating opacity and thus particularly suited for the labelling of surfaces which have to be obscured. Optimal printability and toner keying as well as optimum flatness, even at thermal loads during the printing process.

Grammage	approx. 77 g/m ²	ISO 536		
Caliper	approx. 77 µm	ISO 534		
Tensile strength MD	approx. 63 N/15 mm	DIN 53112	CD approx. 33 N/15 mm	DIN 53112
Stiffness MD	approx. 160 mN	DIN 53121	CD approx. 90 mN	DIN 53121
Opacity	approx. 99 %	ISO 2471		

2. Adhesive

Repositionable special adhesive, solvent-free. Reliable adhesion on a wide range of surfaces (smooth, dry, undamaged, dust-free). Residue-free removal without damaging the surface. Problem-free repositioning, adheres again several times. Free from plasticiser and acid.

Tack	medium
Peel adhesion	low, residue-free removal
Shear	adhesion failure
Minimum application temperature	5 °C
Service Temperature	-10 °C to +40 °C (up to 200 °C for short periods – hot fusing)
Shelf life	2 years (in original package)

3. Release liner

White kraft liner, coated on one side, made of chlorine-free pulp. Designed for all printers and copiers. The reverse of the paper assures excellent processing characteristics, i.e. high friction combined with high abrasion resistance.

Grammage	approx. 73 g/m ²	ISO 536
Caliper	approx. 73 µm	ISO 534

Regulations concerning contact with food: The paper complies with recommendation BfR XXXVI.

4. Packaging

Cardboard packaging, made of recycled cardboard, dispose of as for waste paper. Protects the contents from harm caused by moisture and temperature.