

Trade name: edding OHP-Ink Permanent (blue) contained in: edding 140 S, edding 141 F, edding 142

Current version : 4.2.2, issued: 27.10.2022

Replaced version: 4.2.1, issued: 17.09.2021

Region: GB

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

edding OHP-Ink Permanent (blue) contained in: edding 140 S, edding 141 F, edding 142 M, edding 143 B, edding 147 S, edding 148 F und edding 149 M

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Ink for use in felt pens

Uses advised against

No data available.

1.3 Details of the supplier of the safety data sheet

Address

edding International GmbH

Bookkoppel 7

D-22926 Ahrensburg

Telephone no. +49 (0) 41 02 / 80 8-0

Information provided by / telephone

+49 (0)4102 - 808-0

Advice on Safety Data Sheet

sdb_info@umco.de

1.4 Emergency telephone number

For medical advice (in German and English):

+49 (0)30 30686 790 (Giftnotruf Berlin)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification in accordance with Regulation (EC) No 1272/2008 (CLP)

Flam. Liq. 2; H225

STOT SE 3; H336

Classification information

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)

Hazard pictograms



GHS02



GHS07

Signal word

Danger

Hazardous component(s) to be indicated on label:

1-methoxy-2-propanol

Hazard statement(s)

Trade name: edding OHP-Ink Permanent (blue) contained in: edding 140 S, edding 141 F, edding 142

Current version : 4.2.2, issued: 27.10.2022

Replaced version: 4.2.1, issued: 17.09.2021

Region: GB

H225 Highly flammable liquid and vapour.
H336 May cause drowsiness or dizziness.

Precautionary statement(s)

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P271 Use only outdoors or in a well-ventilated area.
P370+P378 In case of fire: Use water spray, extinguishing powder, foam or CO2 to extinguish.
P405 Store locked up.
P501 Dispose of contents/container to a facility in accordance with local and national regulations.

2.3 Other hazards

No data available.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable. The product is not a substance.

3.2 Mixtures

Chemical characterization

Mixture (preparation)

Hazardous ingredients

No	Substance name	Classification (EC) 1272/2008 (CLP)	Additional information	%
	CAS / EC / Index / REACH no		Concentration	
1	1-methoxy-2-propanol			
	107-98-2 203-539-1 603-064-00-3 01-2119457435-35-0034	Flam. Liq. 3; H226 STOT SE 3; H336	>= 50.00 - < 70.00	wt%
2	ethanol			
	64-17-5 200-578-6 603-002-00-5 01-2119457610-43	Flam. Liq. 2; H225	>= 10.00 - < 25.00	wt%
3	propan-2-ol			
	67-63-0 200-661-7 603-117-00-0 01-2119457558-25-0085	Eye Irrit. 2; H319 Flam. Liq. 2; H225 STOT SE 3; H336	>= 5.00 - < 10.00	wt%

Full Text for all H-phrases and EUH-phrases: pls. see section 16

Additional ingredients

No	Substance name	Classification (EC) 1272/2008 (CLP)	Additional information	%
	CAS / EC / Index / REACH no		Concentration	
1	Reaction mass of hydrogen [1 - [(2-hydroxy-4-nitrophenyl) azo] -2-naphtholato (2 -)] [1 - [(2-hydroxy-5-nitrophenyl) azo] -2-naphtholato (2 -)] Chromate (1-), compound with 3- [(2-ethylhexyl) oxy] propylamine (1: 1) and hydrogen bis [1 - [(2-hydroxy-4-nitrophenyl) azo] -2-naphtholato (2 -)] Chromate (1-), compound with 3- [(2-ethylhexyl) oxy] propylamine (1: 1) and hydrogen bis [1 - [(2-hydroxy-5-nitrophenyl) azo] -2-naphtholato (2 -)] chromate (1-), compound with 3 - [(2-ethylhexyl) oxy] propylamine (1: 1)			

Trade name: edding OHP-Ink Permanent (blue) contained in: edding 140 S, edding 141 F, edding 142

Current version : 4.2.2, issued: 27.10.2022

Replaced version: 4.2.1, issued: 17.09.2021

Region: GB

- 916-881-8 - 01-2120763683-46	-	< 0.50	wt%
---	---	--------	-----

3.3 Other information

The data subject of this Material Safety Data sheet refer to the ink contained in this product (marker).

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In case of persisting adverse effects, consult a physician. Remove contaminated clothing and shoes immediately, and launder thoroughly before reusing.

After inhalation

Remove affected person from the immediate area. Ensure supply of fresh air.

After skin contact

Wash immediately with plenty of water for several minutes.

After eye contact

Remove contact lenses. Rinse eye thoroughly under running water keeping eyelids wide open and protecting the unaffected eye (at least 10 to 15 minutes). Seek medical assistance.

After ingestion

Rinse the mouth thoroughly with water. Call a doctor immediately. Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

No data available.

4.3 Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Foam; Extinguishing powder; Carbon dioxide

Unsuitable extinguishing media

No data available.

5.2 Special hazards arising from the substance or mixture

In the event of fire, the following can be released: Carbon dioxide (CO₂); Carbon monoxide (CO)

5.3 Advice for firefighters

Cool endangered containers with water spray jet. Use self-contained breathing apparatus. Suppress gases/vapours/mists with water spray jet. Wear protective clothing.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Refer to protective measures listed in sections 7 and 8. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Keep away from ignition sources.

For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

6.2 Environmental precautions

Do not discharge into the drains/surface waters/groundwater. Do not discharge into the subsoil/soil.

6.3 Methods and material for containment and cleaning up

Trade name: edding OHP-Ink Permanent (blue) contained in: edding 140 S, edding 141 F, edding 142

Current version : 4.2.2, issued: 27.10.2022

Replaced version: 4.2.1, issued: 17.09.2021

Region: GB

Take up with absorbent material (e.g., sand, kieselguhr, universal binder). When collected, handle material as described under the section heading "Disposal considerations".

6.4 Reference to other sections

No data available.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Provide good ventilation at the work area (local exhaust ventilation, if necessary). If workplace exposure limits are exceeded, respiratory protection approved for this particular job must be worn.

General protective and hygiene measures

Do not eat, drink or smoke during work time. Keep away from foodstuffs and beverages. Avoid contact with eyes and skin. Remove soiled or soaked clothing immediately. Do not inhale vapours. Provide eye wash fountain in work area. Have emergency shower available.

Advice on protection against fire and explosion

Vapours can form an explosive mixture with air. Take precautionary measures against static charges. Keep away from sources of heat and ignition. Use explosion-proof equipment/fittings and non-sparking tools.

7.2 Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions

Keep container tightly closed in a cool, well-ventilated place. Protect from heat and direct sunlight.

Requirements for storage rooms and vessels

Containers which are opened must be carefully closed and kept upright to prevent leakage. Always keep in containers of same material as the original.

7.3 Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

No	Substance name	CAS no.	EC no.
1	1-methoxy-2-propanol	107-98-2	203-539-1
	2000/39/EC		
	1-Methoxypropanol-2		
	WEL short-term (15 min reference period)	568	mg/m ³ 150 ppm
	WEL long-term (8-hr TWA reference period)	375	mg/m ³ 100 ppm
	Skin resorption / sensibilisation	Skin	
	List of approved workplace exposure limits (WELs) / EH40		
	1-Methoxypropan-2-ol		
	WEL short-term (15 min reference period)	560	mg/m ³ 150 ppm
	WEL long-term (8-hr TWA reference period)	375	mg/m ³ 100 ppm
	Comments	Sk	
2	ethanol	64-17-5	200-578-6
	List of approved workplace exposure limits (WELs) / EH40		
	Ethanol		
	WEL long-term (8-hr TWA reference period)	1920	mg/m ³ 1000 ppm
3	propan-2-ol	67-63-0	200-661-7
	List of approved workplace exposure limits (WELs) / EH40		
	Propan-2-ol		
	WEL short-term (15 min reference period)	1250	mg/m ³ 500 ppm
	WEL long-term (8-hr TWA reference period)	999	mg/m ³ 400 ppm

DNEL, DMEL and PNEC values

Trade name: edding OHP-Ink Permanent (blue) contained in: edding 140 S, edding 141 F, edding 142

Current version : 4.2.2, issued: 27.10.2022

Replaced version: 4.2.1, issued: 17.09.2021

Region: GB

DNEL values (worker)

No	Substance name			CAS / EC no	
	Route of exposure	Exposure time	Effect	Value	
1	1-methoxy-2-propanol			107-98-2 203-539-1	
	dermal	Long term (chronic)	systemic	183	mg/kg/day
	inhalative	Long term (chronic)	systemic	369	mg/m ³
	inhalative	Short term (acut)	local	553.5	mg/m ³
2	ethanol			64-17-5 200-578-6	
	dermal	Long term (chronic)	systemic	343	mg/kg/day
	inhalative	Long term (chronic)	systemic	950	mg/m ³
3	propan-2-ol			67-63-0 200-661-7	
	dermal	Long term (chronic)	systemic	888	mg/kg/day
	inhalative	Long term (chronic)	systemic	500	mg/m ³

DNEL value (consumer)

No	Substance name			CAS / EC no	
	Route of exposure	Exposure time	Effect	Value	
1	1-methoxy-2-propanol			107-98-2 203-539-1	
	oral	Long term (chronic)	systemic	33	mg/kg/day
	dermal	Long term (chronic)	systemic	78	mg/kg/day
	inhalative	Long term (chronic)	systemic	43.9	mg/m ³
2	ethanol			64-17-5 200-578-6	
	oral	Long term (chronic)	systemic	87	mg/kg/day
	dermal	Long term (chronic)	systemic	206	mg/kg/day
	inhalative	Short term (acut)	local	950	mg/m ³
	inhalative	Long term (chronic)	systemic	114	mg/m ³
3	propan-2-ol			67-63-0 200-661-7	
	oral	Long term (chronic)	systemic	26	mg/kg/day
	dermal	Long term (chronic)	systemic	319	mg/kg/day
	inhalative	Long term (chronic)	systemic	89	mg/m ³

PNEC values

No	Substance name		CAS / EC no	
	ecological compartment	Type	Value	
1	1-methoxy-2-propanol		107-98-2 203-539-1	
	water	fresh water	10	mg/L
	water	marine water	1	mg/L
	water	Aqua intermittent	100	mg/L
	water	fresh water sediment	52.3	mg/kg
	with reference to: dry weight			
	water	marine water sediment	5.2	mg/kg
	with reference to: dry weight			
	soil	-	4.59	mg/kg
	with reference to: dry weight			
2	ethanol		64-17-5 200-578-6	
	water	fresh water	0.96	mg/L
	water	marine water	0.79	mg/L
	water	fresh water sediment	3.6	mg/kg
	with reference to: dry weight			
	water	Aqua intermittent	2.75	mg/L
	water	marine water sediment	2.9	mg/kg
	with reference to: dry weight			

Trade name: edding OHP-Ink Permanent (blue) contained in: edding 140 S, edding 141 F, edding 142

Current version : 4.2.2, issued: 27.10.2022

Replaced version: 4.2.1, issued: 17.09.2021

Region: GB

	soil	-	0.63	mg/kg
	with reference to: dry weight			
	sewage treatment plant	-	580	mg/L
	secondary poisoning	-	0.38	g/kg
	with reference to: food			
3	propan-2-ol		67-63-0 200-661-7	
	water	fresh water	140.9	mg/L
	water	Aqua intermittent	140.9	mg/L
	water	marine water	140.9	mg/L
	water	fresh water sediment	552	mg/L
	water	marine water sediment	552	mg/L
	soil	-	28	mg/kg
	sewage treatment plant	-	2251	mg/L
	secondary poisoning	-	160	mg/kg
	with reference to: food			

8.2 Exposure controls

Appropriate engineering controls

No data available.

Personal protective equipment

Respiratory protection

If workplace exposure limits are exceeded, a respiration protection approved for this particular job must be worn. In case of aerosol and mist formation, take appropriate measures for breathing protection in the event workplace threshold values are not specified.

Eye / face protection

Safety glasses with side protection shield (EN 166)

Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Other

Normal chemical work clothing.

Environmental exposure controls

No data available.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

State of aggregation	
liquid	
Form	
liquid	
Colour	
blue	
Odour	
weak	
pH value	
No data available	
Boiling point / boiling range	
Value	78 °C
Reference substance	CAS 64-17-5

Trade name: edding OHP-Ink Permanent (blue) contained in: edding 140 S, edding 141 F, edding 142

Current version : 4.2.2, issued: 27.10.2022

Replaced version: 4.2.1, issued: 17.09.2021

Region: GB

Melting point/freezing point			
No data available			
Decomposition temperature			
No data available			
Flash point			
Value		13	°C
Reference substance	CAS 64-17-5		
Ignition temperature			
No data available			
Flammability			
No data available			
Lower explosion limit			
Value		1.9	% vol
Upper explosion limit			
Value		13.1	% vol
Vapour pressure			
No data available			
Relative vapour density			
No data available			
Relative density			
Value		0.938	
Density			
No data available			
Solubility in water			
Comments	insoluble		
Solubility			
No data available			
Partition coefficient n-octanol/water (log value)			
No	Substance name	CAS no.	EC no.
1	propan-2-ol	67-63-0	200-661-7
	log Pow		0.05
	Reference temperature		25 °C
	Source	ECHA	
Kinematic viscosity			
No data available			
Particle characteristics			
No data available			

9.2 Other information

Other information
No data available.

SECTION 10: Stability and reactivity

10.1 Reactivity

No data available.

10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

10.3 Possibility of hazardous reactions

No data available.

Trade name: edding OHP-Ink Permanent (blue) contained in: edding 140 S, edding 141 F, edding 142

Current version : 4.2.2, issued: 27.10.2022

Replaced version: 4.2.1, issued: 17.09.2021

Region: GB

10.4 Conditions to avoid

Heat; air humidity

10.5 Incompatible materials

No data available.

10.6 Hazardous decomposition products

No hazardous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity			
No	Substance name	CAS no.	EC no.
1	1-methoxy-2-propanol	107-98-2	203-539-1
LD50		4016	mg/kg bodyweight
Species	rat		
Method	EC 440/2008, B.1		
Source	ECHA		
2	ethanol	64-17-5	200-578-6
LD50		10740	mg/kg bodyweight
Species	rat		
Method	OECD 401		
Source	ECHA		
3	propan-2-ol	67-63-0	200-661-7
LD50		5840	mg/kg bodyweight
Species	rat		
Method	OECD 401		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Acute dermal toxicity			
No	Substance name	CAS no.	EC no.
1	1-methoxy-2-propanol	107-98-2	203-539-1
LD50		> 2000	mg/kg bodyweight
Species	rat		
Method	440/2008/EC B.3.		
Source	ECHA		

Acute inhalational toxicity			
No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
LC50		124.7	mg/l
Duration of exposure		4	h
State of aggregation	Dust/mist		
Species	rat		
Method	OECD 403		
Source	ECHA		
2	propan-2-ol	67-63-0	200-661-7
LC50		> 10000	ppmV
Duration of exposure		6	h
State of aggregation	Vapour		
Species	rat		
Method	OECD 403		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Skin corrosion/irritation			
No	Substance name	CAS no.	EC no.
1	1-methoxy-2-propanol	107-98-2	203-539-1
Species	rabbit		

Trade name: edding OHP-Ink Permanent (blue) contained in: edding 140 S, edding 141 F, edding 142

Current version : 4.2.2, issued: 27.10.2022

Replaced version: 4.2.1, issued: 17.09.2021

Region: GB

Method	EC 440/2008, B.4		
Source	ECHA		
Evaluation	non-irritant		
2	propan-2-ol	67-63-0	200-661-7
Species	rabbit		
Source	ECHA		
Evaluation	non-irritant		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Serious eye damage/irritation			
No	Substance name	CAS no.	EC no.
1	1-methoxy-2-propanol	107-98-2	203-539-1
Species	rabbit		
Method	2004/73/EEC, B.5		
Source	ECHA		
Evaluation	non-irritant		
2	propan-2-ol	67-63-0	200-661-7
Species	rabbit		
Method	OECD 405		
Source	ECHA		
Evaluation	irritant		
Evaluation/classification	Based on available data, the classification criteria are met.		

Respiratory or skin sensitisation			
No	Substance name	CAS no.	EC no.
1	1-methoxy-2-propanol	107-98-2	203-539-1
Route of exposure	Skin		
Species	guinea pig		
Method	440/2008/EC B.6		
Source	ECHA		
Evaluation	non-sensitizing		
2	ethanol	64-17-5	200-578-6
Route of exposure	Skin		
Species	mouse		
Method	OECD 429		
Source	ECHA		
Evaluation	non-sensitizing		
3	propan-2-ol	67-63-0	200-661-7
Route of exposure	Skin		
Species	guinea pig		
Method	OECD 406		
Source	ECHA		
Evaluation	non-sensitizing		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Germ cell mutagenicity			
No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
2	propan-2-ol	67-63-0	200-661-7
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Reproduction toxicity			
No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Carcinogenicity			
No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6

Trade name: edding OHP-Ink Permanent (blue) contained in: edding 140 S, edding 141 F, edding 142

Current version : 4.2.2, issued: 27.10.2022

Replaced version: 4.2.1, issued: 17.09.2021

Region: GB

Source	ECHA
Evaluation/classification	Based on available data, the classification criteria are not met.

STOT - single exposure

No data available

STOT - repeated exposure

No	Substance name	CAS no.	EC no.
1	propan-2-ol	67-63-0	200-661-7
Route of exposure		inhalational	
Source		ECHA	
Evaluation/classification		Based on available data, the classification criteria are not met.	

Aspiration hazard

No data available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Inhalation of vapours may lead to headache, drowsiness and dizziness. Repeated and prolonged skin contact may cause removal of natural fat from the skin and irritation of the skin. Eye contact with the product may lead to irritation.

11.2 Information on other hazards

Endocrine disrupting properties

No data available.

Other information

No data available.

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish (acute)			
No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
LC50		>	14000 mg/l
Duration of exposure			96 h
Species		Pimephales promelas	
Method		EPA E03-05	
Source		ECHA	
Evaluation/classification		Based on available data, the classification criteria are not met.	
2	propan-2-ol	67-63-0	200-661-7
LC50			9640 mg/l
Duration of exposure			96 h
Species		Pimephales promelas	
Method		OECD 203	
Source		ECHA	

Toxicity to fish (chronic)

No data available

Toxicity to Daphnia (acute)

No	Substance name	CAS no.	EC no.
1	propan-2-ol	67-63-0	200-661-7
EC50		>	10000 mg/l
Duration of exposure			24 h
Species		Daphnia magna	
Method		OECD 202	
Source		ECHA	

Toxicity to Daphnia (chronic)

No data available

Toxicity to algae (acute)

No data available

Trade name: edding OHP-Ink Permanent (blue) contained in: edding 140 S, edding 141 F, edding 142

Current version : 4.2.2, issued: 27.10.2022

Replaced version: 4.2.1, issued: 17.09.2021

Region: GB

Toxicity to algae (chronic)
No data available

Bacteria toxicity
No data available

12.2 Persistence and degradability

Biodegradability			
No	Substance name	CAS no.	EC no.
1	1-methoxy-2-propanol	107-98-2	203-539-1
Type		aerobic biodegradation	
Value		96	%
Duration		28	day(s)
Method		OECD 301 E	
Source		ECHA	
Evaluation		readily biodegradable	
2	propan-2-ol	67-63-0	200-661-7
Type		BOD/COD	
Value		53	%
Duration		5	day(s)
Source		ECHA	
Evaluation		readily biodegradable	

12.3 Bioaccumulative potential

Partition coefficient n-octanol/water (log value)			
No	Substance name	CAS no.	EC no.
1	propan-2-ol	67-63-0	200-661-7
log Pow		0.05	
Reference temperature		25	°C
Source		ECHA	

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

No data available.

12.6 Endocrine disrupting properties

No data available.

12.7 Other adverse effects

No data available.

12.8 Other information

Other information
Do not discharge product unmonitored into the environment.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Allocation of a waste code number, according to the European Waste Catalogue, should be carried out in agreement with the regional waste disposal company.

Packaging

Residues must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer.

SECTION 14: Transport information

14.1 Transport ADR/RID/ADN

Class 3

Trade name: edding OHP-Ink Permanent (blue) contained in: edding 140 S, edding 141 F, edding 142

Current version : 4.2.2, issued: 27.10.2022

Replaced version: 4.2.1, issued: 17.09.2021

Region: GB

Classification code	F1
Packing group	II
Hazard identification no.	33
UN number	UN1263
Proper shipping name	PAINT
Special Provision 640	640D
Tunnel restriction code	D/E
Label	3

14.2 Transport IMDG

Class	3
Packing group	II
UN number	UN1263
Proper shipping name	PAINT
EmS	F-E, S-E
Label	3

14.3 Transport ICAO-TI / IATA

Class	3
Packing group	II
UN number	UN1263
Proper shipping name	Paint
Label	3

14.4 Other information

No data available.

14.5 Environmental hazards

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

14.6 Special precautions for user

No data available.

14.7 Maritime transport in bulk according to IMO instruments

Not relevant

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

REACH candidate list of substances of very high concern (SVHC) for authorisation

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES

The product is considered being subject to REACH regulation (EC) 1907/2006 annex XVII. No 3, 40

The product contains following substance(s) that are considered being subject to REACH regulation (EC) 1907/2006 annex XVII.

No	Substance name	CAS no.	EC no.	No
1	3',6'-bis(diethylamino)spiro[isobenzofuran-1(3H),9'-[9H]xanthene]-3 one, C.I. Solvent Red 49	509-34-2	208-096-8	75
2	propan-2-ol	67-63-0	200-661-7	75

Trade name: edding OHP-Ink Permanent (blue) contained in: edding 140 S, edding 141 F, edding 142

Current version : 4.2.2, issued: 27.10.2022

Replaced version: 4.2.1, issued: 17.09.2021

Region: GB

3	<p>Reaction mass of hydrogen [1 - [(2-hydroxy-4-nitrophenyl) azo] -2-naphtholato (2 -)] [1 - [(2-hydroxy-5-nitrophenyl) azo] -2-naphtholato (2 -)] Chromate (1-), compound with 3- [(2-ethylhexyl) oxy] propylamine (1: 1) and hydrogen bis [1 - [(2-hydroxy-4-nitrophenyl) azo] -2-naphtholato (2 -)] Chromate (1-), compound with 3- [(2-ethylhexyl) oxy] propylamine (1: 1) and hydrogen bis [1 - [(2-hydroxy-5-nitrophenyl) azo] -2-naphtholato (2 -)] chromate (1-), compound with 3 - [(2-ethylhexyl) oxy] propylamine (1: 1)</p>	-	916-881-8	75
---	---	---	-----------	----

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances

This product is subject to Part I of Annex I, risk category:

P5b

15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for this mixture.

SECTION 16: Other information

Sources of key data used to compile the data sheet:

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

Directives 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164.

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding section.

Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)

H226

Flammable liquid and vapour.

H319

Causes serious eye irritation.

Creation of the safety data sheet

UMCO GmbH

Georg-Wilhelm-Str. 187, D-21107 Hamburg

Tel.: +49 40 / 555 546 300 Fax: +49 40 / 555 546 357 e-mail: umco@umco.de

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH.

Prod-ID 21510