

**Trade name:** edding OHP-Ink non-Permanent (blue) contained in: edding 150 S, edding 151 F, edding

**Current version :** 3.0.4, issued: 27.10.2022

**Replaced version:** 3.0.3, issued: 15.09.2021

**Region:** GB

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

#### Trade name

**edding OHP-Ink non-Permanent (blue) contained in: edding 150 S, edding 151 F, edding 152 M, edding 153 B**

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

#### Relevant identified uses of the substance or mixture

Ink for use in felt pens

#### Uses advised against

No data available.

### 1.3 Details of the supplier of the safety data sheet

#### Address

edding International GmbH

Bookkoppel 7

D-22926 Ahrensburg

Telephone no. +49 (0) 41 02 / 80 8-0

#### Information provided by / telephone

+49 (0)4102 - 808-0

#### Advice on Safety Data Sheet

sdb\_info@umco.de

### 1.4 Emergency telephone number

For medical advice (in German and English):

+49 (0)30 30686 790 (Giftnotruf Berlin)

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

#### Classification in accordance with Regulation (EC) No 1272/2008 (CLP)

Aquatic Chronic 3; H412

#### Classification information

EG/1272/2008, 2.6.4.5: "Liquids with a flash point of more than 35 °C need not be classified in Category 3 if negative results have been obtained in the sustained combustibility test L.2, Part III, section 32 of the UN Recommendations on the Transport of Dangerous Goods, Manual of Tests and Criteria."

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

### 2.2 Label elements

#### Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)

#### Hazard pictograms

-

#### Signal word

-

#### Hazard statement(s)

H412 Harmful to aquatic life with long lasting effects.

#### Precautionary statement(s)

P273 Avoid release to the environment.

**Trade name:** edding OHP-Ink non-Permanent (blue) contained in: edding 150 S, edding 151 F, edding

**Current version :** 3.0.4, issued: 27.10.2022

**Replaced version:** 3.0.3, issued: 15.09.2021

**Region:** GB

P501

Dispose of contents/container to a facility in accordance with local and national regulations.

### 2.3 Other hazards

No data available.

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not applicable. The product is not a substance.

### 3.2 Mixtures

#### Chemical characterization

Mixture (preparation)

#### Hazardous ingredients

No	Substance name	Additional information	
	CAS / EC / Index / REACH no	Classification (EC) 1272/2008 (CLP)	Concentration
			%
1	ethanol		pls. refer to footnote (1)
	64-17-5 200-578-6 603-002-00-5 -	Flam. Liq. 2; H225 Eye Irrit. 2; H319	>= 2.50 - <= 10.00 wt%
2	hydrogen [4-[[4-(diethylamino)phenyl][4-[ethyl(3-sulphonatobenzyl)amino]phenyl]methylene]cyclohexa-2,5-dien-1-ylidene](ethyl)(3-sulphonatobenzyl)ammonium, sodium salt C.I. Acid Violet 17		
	4129-84-4 223-942-6 - -	Aquatic Chronic 2; H411	>= 2.50 - <= 10.00 wt%

Full Text for all H-phrases and EUH-phrases: pls. see section 16

(1) Aberrant from/in addition to the classification set out in Annex VI, this substance is classified according to European Regulation (EC) No 1272/2008 (CLP), Article 4 (3), paragraph 2.

No	Note	Specific concentration limits	M-factor (acute)	M-factor (chronic)
1	-	Eye Irrit. 2; H319: C >= 50%	-	-

### 3.3 Other information

The data subject of this Material Safety Data sheet refer to the ink contained in this product (marker).

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### General information

In case of persisting adverse effects, consult a physician. Remove contaminated clothing and shoes immediately, and launder thoroughly before reusing.

#### After inhalation

Ensure supply of fresh air.

#### After skin contact

Wash off immediately with soap and water.

#### After eye contact

Remove contact lenses. Rinse eye thoroughly under running water keeping eyelids wide open and protecting the unaffected eye (at least 10 to 15 minutes). Seek medical assistance.

#### After ingestion

Rinse the mouth thoroughly with water. Call a doctor immediately. Never give anything by mouth to an unconscious person.

### 4.2 Most important symptoms and effects, both acute and delayed

**Trade name:** edding OHP-Ink non-Permanent (blue) contained in: edding 150 S, edding 151 F, edding

**Current version :** 3.0.4, issued: 27.10.2022

**Replaced version:** 3.0.3, issued: 15.09.2021

**Region:** GB

No data available.

#### 4.3 Indication of any immediate medical attention and special treatment needed

No data available.

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

##### Suitable extinguishing media

Alcohol-resistant foam; Carbon dioxide; Extinguishing powder; Water spray jet

##### Unsuitable extinguishing media

High power water jet

#### 5.2 Special hazards arising from the substance or mixture

None known.

#### 5.3 Advice for firefighters

Use self-contained breathing apparatus. Wear protective clothing.

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

##### For non-emergency personnel

Refer to protective measures listed in sections 7 and 8. Avoid contact with skin, eyes and clothing.

##### For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

#### 6.2 Environmental precautions

Do not discharge into the drains/surface waters/groundwater. Do not discharge into the subsoil/soil.

#### 6.3 Methods and material for containment and cleaning up

Take up with absorbent material (e.g., sand, kieselguhr, universal binder). When collected, handle material as described under the section heading "Disposal considerations".

#### 6.4 Reference to other sections

No data available.

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

##### Advice on safe handling

Provide good ventilation at the work area (local exhaust ventilation, if necessary). Observe the usual precautions for handling chemicals.

##### General protective and hygiene measures

Do not eat, drink or smoke during work time. Keep away from foodstuffs and beverages. Avoid contact with eyes and skin. Remove soiled or soaked clothing immediately. Wash hands before breaks and after work.

##### Advice on protection against fire and explosion

Keep away from sources of heat and ignition. Take precautionary measures against static charges.

#### 7.2 Conditions for safe storage, including any incompatibilities

##### Technical measures and storage conditions

Keep container tightly closed and dry in a cool, well-ventilated place.

##### Requirements for storage rooms and vessels

Store product in closed containers.

##### Incompatible products

None known

#### 7.3 Specific end use(s)

No data available.

**Trade name:** edding OHP-Ink non-Permanent (blue) contained in: edding 150 S, edding 151 F, edding

**Current version :** 3.0.4, issued: 27.10.2022

**Replaced version:** 3.0.3, issued: 15.09.2021

**Region:** GB

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limit values

No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
<b>List of approved workplace exposure limits (WELs) / EH40</b>			
Ethanol			
	WEL long-term (8-hr TWA reference period)	1920	mg/m <sup>3</sup> 1000 ppm

### 8.2 Exposure controls

#### **Appropriate engineering controls**

No data available.

#### **Personal protective equipment**

##### **Respiratory protection**

If workplace exposure limits are exceeded, a respiration protection approved for this particular job must be worn. In case of aerosol and mist formation, take appropriate measures for breathing protection in the event workplace threshold values are not specified.

##### **Eye / face protection**

Tightly fitting safety glasses (EN 166).

##### **Hand protection**

In case of intensive contact, wear protective gloves (EN 374). Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

##### **Other**

Normal chemical work clothing.

##### **Environmental exposure controls**

No data available.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

<b>State of aggregation</b>	
liquid	
<b>Form</b>	
liquid	
<b>Colour</b>	
blue	
<b>Odour</b>	
characteristic	
<b>pH value</b>	
Value	5.8
Reference temperature	20 °C
<b>Boiling point / boiling range</b>	
Value	78 °C
<b>Melting point/freezing point</b>	
No data available	
<b>Decomposition temperature</b>	
No data available	

**Trade name:** edding OHP-Ink non-Permanent (blue) contained in: edding 150 S, edding 151 F, edding

**Current version :** 3.0.4, issued: 27.10.2022

**Replaced version:** 3.0.3, issued: 15.09.2021

**Region:** GB

<b>Flash point</b>		
Value	47	°C
<b>Ignition temperature</b>		
Value	425	°C
<b>Auto-ignition temperature</b>		
Comments	Product is not selfigniting.	
<b>Explosive properties</b>		
This product is not explosive. Formation of explosive / highly flammable vapour-air mixtures is possible through use.		
<b>Flammability</b>		
No data available		
<b>Lower explosion limit</b>		
Value	3.5	% vol
<b>Upper explosion limit</b>		
Value	15	% vol
<b>Vapour pressure</b>		
Value	59	hPa
Reference temperature	20	°C
<b>Relative vapour density</b>		
No data available		
<b>Relative density</b>		
No data available		
<b>Density</b>		
Value	1.05	g/cm <sup>3</sup>
Reference temperature	20	°C
<b>Solubility in water</b>		
Comments	Completely miscible	
<b>Solubility</b>		
No data available		
<b>Partition coefficient n-octanol/water (log value)</b>		
No data available		
<b>Kinematic viscosity</b>		
Value	4	s
Reference temperature	20	°C
Type	kinematic	
Method	DIN 53211	
<b>Solvent content</b>		
Value	10.0	%
<b>Solids content</b>		
Value	7.8	%
<b>Particle characteristics</b>		
No data available		

## 9.2 Other information

<b>Other information</b>
No data available.

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No data available.

**Trade name:** edding OHP-Ink non-Permanent (blue) contained in: edding 150 S, edding 151 F, edding

**Current version :** 3.0.4, issued: 27.10.2022

**Replaced version:** 3.0.3, issued: 15.09.2021

**Region:** GB

## 10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

## 10.3 Possibility of hazardous reactions

No data available.

## 10.4 Conditions to avoid

No data available.

## 10.5 Incompatible materials

None known.

## 10.6 Hazardous decomposition products

No hazardous decomposition products known.

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute oral toxicity

No data available

#### Acute dermal toxicity

No data available

#### Acute inhalational toxicity

No data available

#### Skin corrosion/irritation

No data available

#### Serious eye damage/irritation

No data available

#### Respiratory or skin sensitisation

No data available

#### Germ cell mutagenicity

No data available

#### Reproduction toxicity

No data available

#### Carcinogenicity

No data available

#### STOT - single exposure

No data available

#### STOT - repeated exposure

No data available

#### Aspiration hazard

No data available

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

Repeated and prolonged skin contact may cause removal of natural fat from the skin and irritation of the skin. Eye contact with the product may lead to irritation.

### 11.2 Information on other hazards

#### Endocrine disrupting properties

No data available.

#### Other information

No data available.

## SECTION 12: Ecological information

**Trade name:** edding OHP-Ink non-Permanent (blue) contained in: edding 150 S, edding 151 F, edding

**Current version :** 3.0.4, issued: 27.10.2022

**Replaced version:** 3.0.3, issued: 15.09.2021

**Region:** GB

## 12.1 Toxicity

### Toxicity to fish (acute)

No data available

### Toxicity to fish (chronic)

No data available

### Toxicity to Daphnia (acute)

No data available

### Toxicity to Daphnia (chronic)

No data available

### Toxicity to algae (acute)

No data available

### Toxicity to algae (chronic)

No data available

### Bacteria toxicity

No data available

## 12.2 Persistence and degradability

No data available.

## 12.3 Bioaccumulative potential

No data available.

## 12.4 Mobility in soil

No data available.

## 12.5 Results of PBT and vPvB assessment

No data available.

## 12.6 Endocrine disrupting properties

No data available.

## 12.7 Other adverse effects

No data available.

## 12.8 Other information

### Other information

Do not discharge product unmonitored into the environment.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### Product

Allocation of a waste code number, according to the European Waste Catalogue, should be carried out in agreement with the regional waste disposal company.

#### Packaging

Residues must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer.

## SECTION 14: Transport information

### 14.1 Transport ADR/RID/ADN

The product is not subject to ADR/RID/ADN regulations.

### 14.2 Transport IMDG

The product is not subject to IMDG regulations.

### 14.3 Transport ICAO-TI / IATA

**Trade name:** edding OHP-Ink non-Permanent (blue) contained in: edding 150 S, edding 151 F, edding

**Current version :** 3.0.4, issued: 27.10.2022

**Replaced version:** 3.0.3, issued: 15.09.2021

**Region:** GB

The product is not subject to ICAO-TI / IATA regulations.

#### 14.4 Other information

No data available.

#### 14.5 Environmental hazards

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

#### 14.6 Special precautions for user

No data available.

#### 14.7 Maritime transport in bulk according to IMO instruments

Not relevant

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

##### EU regulations

##### **Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)**

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

##### **REACH candidate list of substances of very high concern (SVHC) for authorisation**

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

##### **Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES**

The product is considered being subject to REACH regulation (EC) 1907/2006 annex XVII. No 3

The product contains following substance(s) that are considered being subject to REACH regulation (EC) 1907/2006 annex XVII.

No	Substance name	CAS no.	EC no.	No
1	hydrogen [4-[[4-(diethylamino)phenyl][4-[ethyl(3-sulphonatobenzyl)amino]phenyl]methylene]cyclohexa-2,5-dien-1 ylidene](ethyl)(3-sulphonatobenzyl)ammonium, sodium salt C.I. Acid Violet 17	4129-84-4	223-942-6	75

##### **Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances**

This product is not subject to Part 1 or 2 of Annex I.

#### 15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for this mixture.

### SECTION 16: Other information

#### **Sources of key data used to compile the data sheet:**

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

Directives 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164.

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding section.

#### **Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)**

H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.

#### **Creation of the safety data sheet**



---

**Trade name:** edding OHP-Ink non-Permanent (blue) contained in: edding 150 S, edding 151 F, edding

**Current version :** 3.0.4, issued: 27.10.2022

**Replaced version:** 3.0.3, issued: 15.09.2021

**Region:** GB

---

UMCO GmbH  
Georg-Wilhelm-Str. 187, D-21107 Hamburg  
Tel.: +49 40 / 555 546 300 Fax: +49 40 / 555 546 357 e-mail: umco@umco.de

This information is based on our present knowledge and experience.  
The safety data sheet describes products with a view to safety requirements.  
It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH.  
Prod-ID 19913