

Current version: 3.0.3, issued: 27.10.2022 Replaced version: 3.0.2, issued: 15.09.2021 Region: GB

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### **Product identifier**

Trade name

## edding Boardmarker Ink (pink) contained in: edding 250

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Refill ink

Uses advised against

No data available.

#### 1.3 Details of the supplier of the safety data sheet

edding International GmbH

Bookkoppel 7

D-22926 Ahrensburg

Telephone no. +49 (0) 41 02 / 80 8-0

Information provided by / telephone

+49 (0)4102 - 808-0

**Advice on Safety Data Sheet** 

sdb info@umco.de

## **Emergency telephone number**

For medical advice (in German and English): +49 (0)30 30686 790 (Giftnotruf Berlin)

# **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

### Classification in accordance with Regulation (EC) No 1272/2008 (CLP)

Eye Irrit. 2; H319 Flam. Liq. 2; H225

#### Classification information

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

#### 2.2 Label elements

### Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)

### Hazard pictograms







Signal word

Danger

### Hazard statement(s)

H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation.

### Precautionary statement(s)

P101 If medical advice is needed, have product container or label at hand.



Current version: 3.0.3, issued: 27.10.2022 Replaced version: 3.0.2, issued: 15.09.2021 Region: GB

P102 Keep out of reach of children.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No P210

P370+P378 In case of fire: Use water spray, extinguishing powder, foam or CO2 to extinguish. P501

Dispose of contents/container to a facility in accordance with local and national

regulations.

#### 2.3 Other hazards

No data available.

# **SECTION 3: Composition/information on ingredients**

#### 3.1 **Substances**

Not applicable. The product is not a substance.

#### 3.2 **Mixtures**

#### **Chemical characterization**

Alcoholic solution of organic pigments, binding agents and additives.

**Hazardous ingredients** 

No	Substance name	Substance name		
	CAS / EC / Index /	Classification (EC) 1272/2008 (CLP)	Concentration	%
	REACH no			
1	ethanol		pls. refer to footnote (1)	
	64-17-5 200-578-6 603-002-00-5	Flam. Liq. 2; H225 Eye Irrit. 2; H319	>= 50.00 - < 100.00	wt%
2	1-methoxy-2-propa	nol		
	107-98-2 203-539-1 603-064-00-3	Flam. Liq. 3; H226 STOT SE 3; H336	>= 10.00 - < 25.00	wt%

Full Text for all H-phrases and EUH-phrases: pls. see section 16

<sup>(1)</sup> Aberrant from/in addition to the classification set out in Annex VI, this substance is classified according to European Regulation (EC) No 1272/2008 (CLP), Article 4 (3), paragraph 2.

No	Note	Specific concentration limits	M-factor (acute)	M-factor (chronic)
1	-	Eye Irrit. 2; H319: C >= 50%	-	-

#### 3.3 Other information

The data subject of this Material Safety Data sheet refer to the ink contained in this product (marker).

### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

#### **General information**

In case of persisting adverse effects, consult a physician. Remove contaminated clothing and shoes immediately, and launder thoroughly before reusing.

### After inhalation

Remove affected person from the immediate area. Ensure supply of fresh air.

#### After skin contact

Wash off immediately with soap and water.

#### After eye contact

Remove contact lenses. Rinse eye thoroughly under running water keeping eyelids wide open and protecting the unaffected eye (at least 10 to 15 minutes). Seek medical assistance.

Do not induce vomiting. Call a doctor immediately. Never give anything by mouth to an unconscious person.

#### 4.2 Most important symptoms and effects, both acute and delayed



Current version: 3.0.3, issued: 27.10.2022 Replaced version: 3.0.2, issued: 15.09.2021 Region: GB

No data available.

### 4.3 Indication of any immediate medical attention and special treatment needed

No data available.

# **SECTION 5: Firefighting measures**

### 5.1 Extinguishing media

#### Suitable extinguishing media

Alcohol-resistant foam; Extinguishing powder; Carbon dioxide; Water spray jet

#### Unsuitable extinguishing media

Water

#### 5.2 Special hazards arising from the substance or mixture

In the event of fire, the following can be released: Carbon dioxide (CO2): Carbon monoxide (CO)

### 5.3 Advice for firefighters

Cool endangered containers with water spray jet. Use self-contained breathing apparatus. Suppress gases/vapours/mists with water spray jet. Wear protective clothing.

### **SECTION 6: Accidental release measures**

### 6.1 Personal precautions, protective equipment and emergency procedures

### For non-emergency personnel

Refer to protective measures listed in sections 7 and 8. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Keep away from ignition sources.

#### For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

#### 6.2 Environmental precautions

Do not discharge into the drains/surface waters/groundwater. Do not discharge into the subsoil/soil.

### 6.3 Methods and material for containment and cleaning up

Take up with absorbent material (e.g., sand, kieselguhr, universal binder). Send in suitable containers for recovery or disposal.

### 6.4 Reference to other sections

No data available.

## **SECTION 7: Handling and storage**

### 7.1 Precautions for safe handling

### Advice on safe handling

Provide good ventilation at the work area (local exhaust ventilation, if necessary). If workplace exposure limits are exceeded, respiratory protection approved for this particular job must be worn. Risks inherent to handling the product must be minimised by applying the appropriate protective and preventive measures. Working processes should - so far as possible, according to the state of the art - be designed to rule out bodily contact or the release of hazardous substances.

### General protective and hygiene measures

Do not eat, drink or smoke during work time. Keep away from foodstuffs and beverages. Avoid contact with eyes and skin. Remove soiled or soaked clothing immediately. Do not inhale vapours. Clean skin thoroughly after work; apply skin cream.

### Advice on protection against fire and explosion

Vapours can form an explosive mixture with air. Take precautionary measures against static charges. Keep away from sources of heat and ignition. Use explosion-proof equipment/fittings and non-sparking tools.

### 7.2 Conditions for safe storage, including any incompatibilities

### Technical measures and storage conditions

Keep container tightly closed and dry in a cool, well-ventilated place. Protect from heat and direct sunlight.

### Requirements for storage rooms and vessels



Current version: 3.0.3, issued: 27.10.2022 Replaced version: 3.0.2, issued: 15.09.2021 Region: GB

Containers which are opened must be carefully closed and kept upright to prevent leakage. Always keep in containers of same material as the original.

### 7.3 Specific end use(s)

No data available.

### **SECTION 8: Exposure controls/personal protection**

### 8.1 Control parameters

### Occupational exposure limit values

No	Substance name	CAS no.		EC no.	
1	ethanol 64-17-5			200-578-6	
	List of approved workplace exposure limits (WELs) / E	EH40			
	Ethanol				
	WEL long-term (8-hr TWA reference period)	1920	mg/m³	1000	ppm
2	1-methoxy-2-propanol	107-98-2		203-539-1	
	2000/39/EC				
	1-Methoxypropanol-2				
	WEL short-term (15 min reference period)	568	mg/m³	150	ppm
	WEL long-term (8-hr TWA reference period)	375	mg/m³	100	ppm
	Skin resorption / sensibilisation	Skin			
	List of approved workplace exposure limits (WELs) / EH40				
	1-Methoxypropan-2-ol				
	WEL short-term (15 min reference period)	560	mg/m³	150	ppm
	WEL long-term (8-hr TWA reference period)	375	mg/m³	100	ppm
	Comments	Sk			

### 8.2 Exposure controls

### Appropriate engineering controls

No data available.

### Personal protective equipment

### Respiratory protection

If workplace exposure limits are exceeded, a respiration protection approved for this particular job must be worn. In case of aerosol and mist formation, take appropriate measures for breathing protection in the event workplace threshold values are not specified.

### Eye / face protection

Safety glasses with side protection shield (EN 166)

#### Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific workstation suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

#### Other

Normal chemical work clothing.

#### **Environmental exposure controls**

No data available.

State of aggregation

### **SECTION 9: Physical and chemical properties**

### 9.1 Information on basic physical and chemical properties

liquid	
Form	
liquid	



Current version: 3.0.3, issued: 27.10.2022 Replaced version: 3.0.2, issued: 15.09.2021 Region: GB

Calaur			
<b>Colour</b> pink			
Odour			
characteristic			
pH value			
No data available			
Boiling point / boiling range			
Value		78	°C
Melting point/freezing point  No data available			
Decomposition temperature			
No data available			
Flash point			
Value		13	°C
Ignition temperature Value		207	00
	1	287	°C
Auto-ignition temperature Comments	Product is not self	ianitina	
	T Toddot is flot sell	iginting.	
Explosive properties The product is not explosive. Formation of explo	sive/highly flammab	le air-vap	oour mixtures is possible during/after use.
Flammability			
No data available			
Lower explosion limit			
Value		1.7	% vol
Upper explosion limit Value		15.0	% vol
		15.0	76 VOI
Vapour pressure Value		59	hPa
Relative vapour density	•		
No data available			
Relative density			
No data available			
Density No data available			
Solubility in water Comments	miscible		
Solubility			
No data available			-
Partition coefficient n-octanol/water (log value) No data available	ie)		
Kinematic viscosity No data available			
Solvent content			
Value		79.1	%
Particle characteristics No data available			



Current version: 3.0.3, issued: 27.10.2022 Replaced version: 3.0.2, issued: 15.09.2021 Region: GB

#### 9.2 Other information

Other information
No data available.

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No data available.

### 10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

### 10.3 Possibility of hazardous reactions

No data available.

#### 10.4 Conditions to avoid

No data available.

### 10.5 Incompatible materials

No data available.

### 10.6 Hazardous decomposition products

No hazardous decomposition products known.

## **SECTION 11: Toxicological information**

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity				
No	Substance name	CAS no.		EC no.
1	1-methoxy-2-propanol	107-98-2		203-539-1
LD5	0		5660	mg/kg bodyweight
Species		rat		
Source		Manufacturer		

Acu	Acute dermal toxicity				
No	Substance name	CAS no.		EC no.	
1	1-methoxy-2-propanol	107-98-2		203-539-1	
LD5	0		9999.99	mg/kg bodyweight	
Species		rabbit			
Source		Manufacturer			

# Acute inhalational toxicity No data available

# Skin corrosion/irritation No data available

# Serious eye damage/irritation No data available

Respiratory or skin sensitisation
No data available

Germ cell mutagenicity	
No data available	

Reproduction toxicity	
No data available	

Carcinogenicity	
No data available	

STOT - single exposure	
No data available	



Current version: 3.0.3, issued: 27.10.2022 Replaced version: 3.0.2, issued: 15.09.2021 Region: GB

### STOT - repeated exposure

No data available

### **Aspiration hazard**

No data available

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

Inhalation of solvent vapours in higher concentration may lead to nausea, headache, drowsiness and dizziness. Repeated and prolonged skin contact may cause removal of natural fat from the skin and irritation of the skin. Eye contact with the product may lead to irritation.

### 11.2 Information on other hazards

### **Endocrine disrupting properties**

No data available.

#### Other information

No data available.

### **SECTION 12: Ecological information**

### 12.1 Toxicity

### Toxicity to fish (acute)

No data available

### Toxicity to fish (chronic)

No data available

### **Toxicity to Daphnia (acute)**

No data available

### **Toxicity to Daphnia (chronic)**

No data available

### Toxicity to algae (acute)

No data available

### Toxicity to algae (chronic)

No data available

#### **Bacteria toxicity**

No data available

### 12.2 Persistence and degradability

No data available.

### 12.3 Bioaccumulative potential

No data available.

### 12.4 Mobility in soil

No data available.

### 12.5 Results of PBT and vPvB assessment

No data available.

# 12.6 Endocrine disrupting properties

No data available.

#### 12.7 Other adverse effects

No data available

### 12.8 Other information

## Other information

Do not discharge product unmonitored into the environment.

# **SECTION 13: Disposal considerations**



Current version: 3.0.3, issued: 27.10.2022 Replaced version: 3.0.2, issued: 15.09.2021 Region: GB

#### 13.1 Waste treatment methods

#### **Product**

Allocation of a waste code number, according to the European Waste Catalogue, should be carried out in agreement with the regional waste disposal company.

#### **Packaging**

Residues must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer.

# **SECTION 14: Transport information**

### 14.1 Transport ADR/RID/ADN

Class 3
Classification code F1
Packing group II
Hazard identification no. 33
UN number UN1263
Proper shipping name PAINT
Special Provision 640 640C
Tunnel restriction code D/E
Label 3

### 14.2 Transport IMDG

Class 3
Packing group II
UN number UN1263
Proper shipping name PAINT
EmS F-E, S-E
Label 3

### 14.3 Transport ICAO-TI / IATA

Class 3
Packing group II
UN number UN1263
Proper shipping name Paint
Label 3

### 14.4 Other information

No data available.

#### 14.5 Environmental hazards

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

### 14.6 Special precautions for user

No data available.

### 14.7 Maritime transport in bulk according to IMO instruments

Not relevant

### **SECTION 15: Regulatory information**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU regulations

## Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

### REACH candidate list of substances of very high concern (SVHC) for authorisation



Current version: 3.0.3, issued: 27.10.2022 Replaced version: 3.0.2, issued: 15.09.2021 Region: GB

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES

The product is considered being subject to REACH regulation (EC) 1907/2006 annex XVII. No 3, 40

### Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances

This product is subject to Part I of Annex I, risk category:

P5b

### 15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for this mixture.

### **SECTION 16: Other information**

#### Sources of key data used to compile the data sheet:

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

Directives 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164.

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding section

# Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)

H226 Flammable liquid and vapour.
H336 May cause drowsiness or dizziness.

### Creation of the safety data sheet

UMCO GmbH

Georg-Wilhelm-Str. 187, D-21107 Hamburg

Tel.: +49 40 / 555 546 300 Fax: +49 40 / 555 546 357 e-mail: umco@umco.de

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH. Prod-ID 615286