

Current version: 2.3.1, issued: 27.10.2022 Replaced version: 2.3.0, issued: 22.10.2015 Region: GB

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 **Product identifier**

Trade name

Boardmarker refill ink 119504, 119904 (green) contained in: TZ 140

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Refill ink

Uses advised against

No data available.

1.3 Details of the supplier of the safety data sheet

Legamaster International B.V.

Kwinkweerd 62

Postbus 111

AC Lochem 7240

The Netherlands

Telephone no. +31 (0) 573-713000

Information provided by / telephone

+31 (0) 573-713000

Advice on Safety Data Sheet

sdb info@umco.de

1.4 **Emergency telephone number**

For medical advice (in German and English):

+49 (0)30 30686 790 (Giftnotruf Berlin)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification in accordance with Regulation (EC) No 1272/2008 (CLP)

Eye Dam. 1; H318

Flam. Liq. 2; H225

STOT SE 3; H336

Classification information

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)

Hazard pictograms





GHS05



GHS02

Signal word

Hazardous component(s) to be indicated on label:

propan-1-ol



Current version: 2.3.1, issued: 27.10.2022 Replaced version: 2.3.0, issued: 22.10.2015 Region: GB

Hazard statement(s)

H225 Highly flammable liquid and vapour.
H318 Causes serious eye damage.
H336 May cause drowsiness or dizziness.

Precautionary statement(s)

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smokina

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P370+P378 In case of fire: Use water spray, extinguishing powder, foam or CO2 to extinguish.

P405 Store locked up.

P501 Dispose of contents/container to a facility in accordance with local and national

regulations.

2.3 Other hazards

No data available.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable. The product is not a substance.

3.2 Mixtures

Chemical characterization

Mixture (preparation)

Hazardous ingredients

No	Substance name		Λdditi	onal information	'n	
140	CAS / EC / Index / Classification (EC) 1272/2008 (CLP)		Concentration			%
	REACH no					, ,
1	propan-1-ol					
	71-23-8	Eye Dam. 1; H318	>=	50.00 - <	100.00	wt%
	200-746-9	Flam. Liq. 2; H225				
	603-003-00-0	STOT SE 3; H336				
	-					
2	propan-2-ol					
	67-63-0	Eye Irrit. 2; H319	>=	2.50 - <=	10.00	wt%
	200-661-7	Flam. Liq. 2; H225				
	603-117-00-0	STOT SE 3; H336				
	-					
3	1-methoxy-2-propa	nol				
	107-98-2	Flam. Liq. 3; H226	>=	2.50 - <=	10.00	wt%
	203-539-1	STOT SE 3; H336				
	603-064-00-3					
	-					

Full Text for all H-phrases and EUH-phrases: pls. see section 16

3.3 Other information

The data subject of this Material Safety Data sheet refer to the ink contained in this product (marker).

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In case of persisting adverse effects, consult a physician. Remove contaminated clothing and shoes immediately, and launder thoroughly before reusing. Poisonous symptoms can first be observed after several hours, therefore medical observation for at least 48 hours is necessary.



Current version: 2.3.1, issued: 27.10.2022 Replaced version: 2.3.0, issued: 22.10.2015 Region: GB

After inhalation

Remove affected person from the immediate area. Ensure supply of fresh air.

After skin contact

Wash off immediately with soap and water.

After eve contact

Remove contact lenses. Rinse eye thoroughly under running water keeping eyelids wide open and protecting the unaffected eye (at least 10 to 15 minutes). Seek medical assistance.

After ingestion

Do not induce vomiting. Call a doctor immediately. Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

No data available.

4.3 Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam; Extinguishing powder; Carbon dioxide; Water spray jet

Unsuitable extinguishing media

High power water jet

5.2 Special hazards arising from the substance or mixture

In the event of fire, the following can be released: Carbon dioxide (CO2); Carbon monoxide (CO)

5.3 Advice for firefighters

Cool endangered containers with water spray jet. Use self-contained breathing apparatus. Suppress gases/vapours/mists with water spray jet. Wear protective clothing.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Refer to protective measures listed in sections 7 and 8. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Keep away from ignition sources.

For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

6.2 Environmental precautions

Do not discharge into the drains/surface waters/groundwater. Do not discharge into the subsoil/soil.

6.3 Methods and material for containment and cleaning up

Take up with absorbent material (e.g., sand, kieselguhr, universal binder). Send in suitable containers for recovery or disposal.

6.4 Reference to other sections

No data available.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Provide good ventilation at the work area (local exhaust ventilation, if necessary). If workplace exposure limits are exceeded, respiratory protection approved for this particular job must be worn. Risks inherent to handling the product must be minimised by applying the appropriate protective and preventive measures. Working processes should - so far as possible, according to the state of the art - be designed to rule out bodily contact or the release of hazardous substances.

General protective and hygiene measures



Current version: 2.3.1, issued: 27.10.2022 Replaced version: 2.3.0, issued: 22.10.2015 Region: GB

Do not eat, drink or smoke during work time. Keep away from foodstuffs and beverages. Avoid contact with eyes and skin. Remove soiled or soaked clothing immediately. Do not inhale vapours. Clean skin thoroughly after work; apply skin cream.

Advice on protection against fire and explosion

Vapours can form an explosive mixture with air. Take precautionary measures against static charges. Keep away from sources of heat and ignition.

7.2 Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions

Keep container tightly closed and dry in a cool, well-ventilated place. Protect from heat and direct sunlight.

Requirements for storage rooms and vessels

Containers which are opened must be carefully closed and kept upright to prevent leakage. Always keep in containers of same material as the original.

Incompatible products

None known

7.3 Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

No	Substance name	CAS no.		EC no.			
1	propan-1-ol	71-23-8		200-746-9			
	List of approved workplace exposure limits (WELs) / EH40						
	Propan-1-ol						
	WEL short-term (15 min reference period)	625	mg/m³	250	ppm		
	WEL long-term (8-hr TWA reference period)	500	mg/m³	200	ppm		
	Comments	Sk					
2	propan-2-ol	67-63-0		200-661-7			
	List of approved workplace exposure limits (WELs) / E	H40					
	Propan-2-ol						
	WEL short-term (15 min reference period)	1250	mg/m³	500	ppm		
	WEL long-term (8-hr TWA reference period)	999	mg/m³	400	ppm		
3	1-methoxy-2-propanol	107-98-2		203-539-1			
	2000/39/EC						
	1-Methoxypropanol-2						
	WEL short-term (15 min reference period)	568	mg/m³	150	ppm		
	WEL long-term (8-hr TWA reference period)	375	mg/m³	100	ppm		
	Skin resorption / sensibilisation	Skin					
	List of approved workplace exposure limits (WELs) / EH40						
,	1-Methoxypropan-2-ol						
	WEL short-term (15 min reference period)	560	mg/m³	150	ppm		
	WEL long-term (8-hr TWA reference period)	375	mg/m³	100	ppm		
	Comments	Sk					

8.2 Exposure controls

Appropriate engineering controls

No data available.

Personal protective equipment

Respiratory protection

If workplace exposure limits are exceeded, a respiration protection approved for this particular job must be worn. In case of aerosol and mist formation, take appropriate measures for breathing protection in the event workplace threshold values are not specified.

Eye / face protection

Safety glasses with side protection shield (EN 166)



Current version: 2.3.1, issued: 27.10.2022 Replaced version: 2.3.0, issued: 22.10.2015 Region: GB

Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific workstation suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Other

Normal chemical work clothing.

Environmental exposure controls

No data available.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

State of aggregation liquid			
Form liquid			
Colour green			
Odour characteristic			
pH value No data available			
Boiling point / boiling range Value		82	°C
Melting point/freezing point No data available			
Decomposition temperature No data available			
Flash point Value		13	°C
Ignition temperature Value		287	°C
Auto-ignition temperature Comments	Product is not selfig	ıniting.	
Explosive properties The product is not explosive. Formation of explosive.	sive/highly flammable	air-vap	our mixtures is possible during/after use.
Flammability No data available			
Lower explosion limit Value		2.1	% vol
Upper explosion limit Value		13.5	% vol
Vapour pressure Value Reference temperature		19 20	hPa °C
Relative vapour density			



Current version: 2.3.1, issued: 27.10.2022 Replaced version: 2.3.0, issued: 22.10.2015 Region: GB

No data available

Relative density
No data available

Density
no data available

Solubility in water

Comments partially miscible

Solubility
No data available

Partition coefficient n-octanol/water (log value)

No data available

 Kinematic viscosity

 Value
 11.5 mPa*s

 Reference temperature
 20 °C

 Type
 dynamic

Value 81.3 %

Solids contentValue6.5 %

Particle characteristics
No data available

9.2 Other information

Other information

No data available.

SECTION 10: Stability and reactivity

10.1 Reactivity

No data available.

10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

10.3 Possibility of hazardous reactions

No data available.

10.4 Conditions to avoid

No data available.

10.5 Incompatible materials

No data available.

10.6 Hazardous decomposition products

No hazardous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acu	te oral toxicity		
No	Substance name	CAS no.	EC no.
1	propan-1-ol	71-23-8	200-746-9
LD50	0	8000	mg/kg bodyweight
Spec	cies	rat	
Sour	rce	Manufacturer	
2	propan-2-ol	67-63-0	200-661-7



Current version: 2.3.1, issued: 27.10.2022 Replaced version: 2.3.0, issued: 22.10.2015 Region: GB

LD5	0		5280	mg/kg bodyweight		
Spe	cies	rat				
Soul	rce	Manufacturer				
3	1-methoxy-2-propanol	107-98-2		203-539-1		
LD5	0		5660	mg/kg bodyweight		
Spe	cies	rat				
Soul	rce	Manufacturer				
_						
Acu	te dermal toxicity					
No	Substance name	CAS no.		EC no.		
1	propan-1-ol	71-23-8		200-746-9		

Acu	te dermal toxicity				
No	Substance name		CAS no.		EC no.
1	propan-1-ol		71-23-8		200-746-9
LD5	0			4000	mg/kg bodyweight
Spec	cies	rabbit			
Soul	rce	Manufacturer			
2	propan-2-ol		67-63-0		200-661-7
LD5	0			12800	mg/kg bodyweight
Spec	cies	rabbit			
Soul	rce	Manufacturer			
3	1-methoxy-2-propanol		107-98-2		203-539-1
LD5	0			9999.99	mg/kg bodyweight
Spec	cies	rabbit			
Soul	rce	Manufacturer			

Acute in	nhalational toxicity					
No Su	ibstance name		CAS no.		EC no.	
1 pro	opan-1-ol		71-23-8		200-746-9	
LC50		>		33.8	mg/l	
Duration	n of exposure			4	h	
State of	aggregation	Vapour				
Species	3	rat				
Method		OECD 403				
Source		ECHA				
2 pro	opan-2-ol		67-63-0		200-661-7	
LC50				72.6	mg/l	
Duration of exposure				4	h	
State of	State of aggregation					
Species		rat				
Source		Manufacturer				

Skin corrosion/irritation	
No data available	

Serious eye damage/irritation No data available

Respiratory or skin sensitisation	
No data available	

Germ cell mutagenicity	
No data available	

Reproduction toxicity	
No data available	

Carcinogenicity	
No data available	

STOT - single exposure
No data available

STOT - repeated exposure	
No data available	
110 data available	

Aspiration hazard		
No data available		



Current version: 2.3.1, issued: 27.10.2022 Replaced version: 2.3.0, issued: 22.10.2015 Region: GB

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Inhalation of solvent vapours in higher concentration may lead to nausea, headache, drowsiness and dizziness. Repeated and prolonged skin contact may cause removal of natural fat from the skin and irritation of the skin. Eye contact with the product may lead to irritation.

11.2 Information on other hazards

Endocrine disrupting properties

No data available.

Other information

No data available.

SECTION 12: Ecological information

12.1 Toxicity

Toxi	Toxicity to fish (acute)						
No	Substance name	CAS no.		EC no.			
1	propan-2-ol	67-63-0		200-661-7			
LC50			9640	mg/l			
Duration of exposure			96	h			
Species		Pimephales promelas					
Source		Manufacturer					

Toxicity to fish (chronic)

No data available

Toxicity to Daphnia (acute)						
No	Substance name	CAS no.		EC no.		
1	propan-2-ol	67-63-0		200-661-7		
EC50			13299	mg/l		
Duration of exposure			48	h		
Species		Daphnia magna				
Source		Manufacturer				

Toxicity to Daphnia (chronic)

No data available

Toxi	Toxicity to algae (acute)					
No	Substance name	C.	AS no.	EC no.		
1	propan-2-ol	67	7-63-0	200-661-7		
EC50		>	1000	mg/l		
Duration of exposure			72	h		
Species		Desmodesmus	subspicatus			
Source		Manufacturer				

Toxicity to algae (chronic)

No data available

Bacteria toxicity

No data available

12.2 Persistence and degradability

Biod	Biodegradability					
No	Substance name	ostance name CAS no.		EC no.		
1	propan-2-ol	67-63-0		200-661-7		
Value			95	%		
Duration			21	day(s)		
Method		OECD 301 E				
Source		Manufacturer				
Evaluation		readily biodegradable				

12.3 Bioaccumulative potential

No data available.



Current version: 2.3.1, issued: 27.10.2022 Replaced version: 2.3.0, issued: 22.10.2015 Region: GB

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

No data available.

12.6 Endocrine disrupting properties

No data available.

12.7 Other adverse effects

No data available.

12.8 Other information

Other information

Do not discharge product unmonitored into the environment.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Allocation of a waste code number, according to the European Waste Catalogue, should be carried out in agreement with the regional waste disposal company.

Packaging

Residues must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer.

SECTION 14: Transport information

14.1 Transport ADR/RID/ADN

Class 3
Classification code F1
Packing group II
Hazard identification no. 33
UN number UN1263

Proper shipping name PAINT RELATED MATERIAL

Special Provision 640 640D Tunnel restriction code D/E Label 3

14.2 Transport IMDG

Class 3
Packing group II
UN number UN1263

Proper shipping name PAINT RELATED MATERIAL

EmS F-E, S-E Label 3

14.3 Transport ICAO-TI / IATA

Class 3
Packing group II
UN number UN1263

Proper shipping name Paint related material

Label 3

14.4 Other information

No data available.

14.5 Environmental hazards

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

14.6 Special precautions for user

No data available.



Current version: 2.3.1, issued: 27.10.2022 Replaced version: 2.3.0, issued: 22.10.2015 Region: GB

14.7 Maritime transport in bulk according to IMO instruments

Not relevant

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU regulations

Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

REACH candidate list of substances of very high concern (SVHC) for authorisation

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES

The product is considered being subject to REACH regulation (EC) 1907/2006 annex XVII. No 3, 40

The product contains following substance(s) that are considered being subject to REACH regulation (EC) 1907/2006 annex XVII.

No	Substance name	CAS no.	EC no.	No
1	propan-1-ol	71-23-8	200-746-9	75
2	propan-2-ol	67-63-0	200-661-7	75

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances		
This product is subject to Part I of Annex I, risk category:	P5b	

15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for this mixture.

SECTION 16: Other information

Sources of key data used to compile the data sheet:

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

Directives 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164.

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding section.

Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)

H226 Flammable liquid and vapour. H319 Causes serious eye irritation.

Creation of the safety data sheet

UMCO GmbH

Georg-Wilhelm-Str. 187, D-21107 Hamburg

Tel.: +49 40 / 555 546 300 Fax: +49 40 / 555 546 357 e-mail: umco@umco.de

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

Alterations/supplements:

Alterations to the previous edition are marked in the left-hand margin.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH. Prod-ID 643859

EU safety data sheet



Trade name: Boardmarker refill ink 119504, 119904 (green) contained in: TZ 140

Current version: 2.3.1, issued: 27.10.2022 Replaced version: 2.3.0, issued: 22.10.2015 Region: GB